

Matrix-DL3705

10W IP65 355D Tiltable LED downlight

Description

Deep Recessed Slim Trim Downlight
Gyro Titable Add-on Honey comb louver
IP65

Finish
Black/White

Material
Aluminium



TECHNICAL CHARACTERISTICS

Light source

Light source: CLU7A3-1201
Output (W): 9W (250mA 36V)
Total power consumption (W): 10W
Color temperature: 2700K/3000K/4000K
CRI: 90
Photobiological risk: RG1
Real Lumen: 700lm
Qty Leds: 1pc
Lm/Real W: 70lm
Life Time: 50.000h L80B20
MacAdam steps: 3
UGR: 19

Gear

This product is supplied without gear;
Recommended gear:
Actec Triac Dimmable driver
D26012NTF

Luminaire


Downlight suitable for outdoor area
crossing: No
Warranty: 5 Years

MATRIX DL3705-SRW

MATRIX DL3705-SSW

MATRIX DL3705-SRB

MATRIX DL3705-SSB



70mm
5-25mm



LIGHT DISTRIBUTION for 3000K Medium 36°

h(m)	E(lx)	Ø(m)
1	1019.2	Ø6.60
2	254.9	Ø1.32
3	113.3	Ø1.98
4	63.71	Ø2.64
5	40.78	Ø3.30

The photograph may not match the reference exactly. Please read the product description to identify the finish.